



Machos STI V-COIL rapid

para Insertos roscados ISO 2 (6H)

STI-Machos V-COIL rapid

para insertos roscados conforme ISO 2 (6H)



Forma D

HSS-G

Tol. ISO 1 (4H)

M

diametro nominal D Tamanho nominal D	B	L 1	L 2	⬡	Art.-No.
M 2.5 x 0.45	3.1	36.0	11.0	1/4"	03090
M 3 x 0.5	3.6	36.0	11.0	1/4"	03091
M 4 x 0.7	4.9	36.0	13.0	1/4"	03092
M 5 x 0.8	6.0	36.0	16.0	1/4"	03093
M 6 x 1.0	7.3	36.0	17.0	1/4"	03094
M 8 x 1.25	9.6	42.0	20.0	1/4"	03095
M 10 x 1.5	11.9	50.0	24.0	1/4"	03096
M 12 x 1.75	14.3	50.0	29.0	1/4"	03097

Brocas STI V-COIL rapid

STI-Brocas V-COIL rapid



diametro nominal D Tamanho nominal D	L 1	S 2	⬡	Art.-No.
2.6 mm	36.0	16.0	1/4"	03080
3.2 mm	36.0	16.0	1/4"	03081
4.2 mm	36.0	16.0	1/4"	03082
5.2 mm	46.0	26.0	1/4"	03083
6.3 mm	46.0	26.0	1/4"	03084
8.3 mm	46.0	26.0	1/4"	03085
10.4 mm	50.0	33.5	1/4"	03086
12.4 mm	50.0	33.5	1/4"	03087