



Hand Taps

metric ISO-thread DIN 13

Rougher piloted

Maschi a mano

filettatura metrica ISO DIN 13

Sgrosso con guida



DIN 352

HSS-E

ToI. ISO2/6H

M

Nominal Diameter D	L 1	L 2	D 2	∅	Art.-No.
M 3 x 0.5	40	11	3.5	2.7	57726
M 4 x 0.7	45	13	4.5	3.4	57730
M 5 x 0.8	50	16	6.0	4.9	57734
M 6 x 1.0	50	19	6.0	4.9	57738
M 8 x 1.25	56	22	6.0	4.9	57742
M 10 x 1.5	70	24	7.0	5.5	57746
M 12 x 1.75	75	29	9.0	7.0	57750

Application:

wear resistant steel up to 1400 N/mm²

- high alloy steel
- heat resistant steel
- stainless steel
- alloy tool steel
- cast iron

Surface treatment: steam tempered

Applicazione:

Acciaio ad alta resistenza R a 1.400 N/mm²

- Acciaio alto legato
- Acciaio resistenti al calore
- Acciaio inossidabili
- Acciaio per utensili legato
- Ghisia grigia

Superficie: vaporizzato

How to order / esempio come ordinare:

- M 3 = 57726
- M 3, No. 1 = 57726-1
- M 3, No. 2 = 57726-2
- M 3, No. 3 = 57726-3

